



RED LINE PROFESSIONAL-SERIES 5W30 MOTOR OIL



- Full-synthetic, OEM-certified formula provides excellent low-temperature flow during cold starts
- Helps to prevent low-speed pre-ignition (LSPI) in turbocharged gas direct-injection engines
- Resistant to oxidation to avoid sludge and has low volatility for reduced oil consumption and longer drain intervals
- Developed to protect against turbocharger deposits and protects emission control system catalysts
- Can be used in vehicles powered by ethanol-containing fuels up to E85

APPROVED / CERTIFIED:

API SN Plus with Resource Conserving

ILSAC GF-5

dexos1™ Gen 2

RECOMMENDED FOR:

CHRYSLER
MS-6395

FORD
WSS-M2C946-A
WSS-M2C946-B1

GM
GM4718M
GM6094M

HONDA/ACURA
HTO-06

TYPICAL PROPERTIES:

API Service Class	SN PLUS
SAE Viscosity Grade (Motor Oil)	5W-30
Vis @ 100°C, cSt	11.0
Vis @ 40°C, cSt	64
Viscosity Index	165
CCS Viscosity, Poise, @ °C	50@-30
Freezing Point °C	-40
Freezing Point °F	-40
HTHS Vis, cP @150°C, ASTM D4741	3.2

PACKAGE SIZES:

- 12204 - 5W30 Prof-Series - quart
- 12205 - 5W30 Prof-Series - 5 quart
- 12208 - 5W30 Prof-Series - 55 gallon

ABOUT RED LINE PROFESSIONAL-SERIES MOTOR OIL

- FULL SYNTHETIC -- OEM-required Group III/Group IV PAO Base Stocks
- Low volatility for reduced oil consumption
- Long-life certification for reduced wear protection following factory drain intervals
- For high- and low-mileage engines
- Compatible with conventional and synthetic oils
- Withstands extreme temperatures

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM